

OTC Website Find Technologies Contact Us

Request Information Permalink

All-Analog Radio Interference Cancellation using CAPS Method

Tech ID: 24023 / UC Case 2013-901-0

CONTACT Venkata S K

Venkata S. Krishnamurty
venkata.krishnamurty@ucr.edu
tel:

BRIEF DESCRIPTION

Full duplex wireless networks offer the capability of transmitting and receiving data at the same time over the same frequency channel and doubling the efficiency of the bandwidth. However, full duplex radios have been limited due to a fundamental issue known as self-interference cancelation (SIC). For SIC, there are four stages which can be used in sequence for maximum benefit: passive interference suppression, all-analog interference cancelation, hybrid interference cancelation, and all-digital interference cancelation.


OTHER INFORMATION

KEYWORDS

interference, cancellation, wireless, all-analog interference, self-

interference cancellation

FULL DESCRIPTION



TOLL DEGOTAL TION

Configuration of radio interference cancelation using CAPS (cables, attenuators and power splitters), which cancels the self-interference from the transmitter to the receiver.

CATEGORIZED AS

- **▶** Communications
 - ▶ Internet
 - Networking
 - Wireless

RELATED CASES

2013-901-0

University of California researchers have developed a new design for all-analog radio SIC using elementary components used in a new design of cables, attenuators, and power splitters. The CAPS method uses an all-analog cancelation channel using cables, attenuators, and power splitters.

ADVANTAGES

- □No requirement for use of any phase-shift.
- ☐ Handles real-time tuning in the presence of unknown distortion functions.
- □ Readily applicable for radio interference cancelation at cellular base stations and vehicle based radios where interference cancelation is high and physical space exists for the required hardware.
- □Potential integration into a single small size unit for low power radio devices, such as smart phones.

OTHER INFORMATION

Applications

□Radio interference cancelation between two or more radios	
□Inter-cell interference cancelation between cellular base stations.	

☐Multiple Input and Multiple Output (MIMO) radios

RELATED MATERIALS

▶ Breaking the Barrier of Transmission Noise in Full-Duplex Radio - 05/31/2013

PATENT STATUS

Country	Туре	Number	Dated	Case
United States Of America	Issued Patent	9,906,262	02/27/2018	2013-901

University of California, Riverside

Office of Technology Commercialization

200 University Office Building,

Riverside,CA 92521

otc@ucr.edu

research.ucr.edu/

Terms of use | Privacy Notice | © 2014 - 2023, The Regents of the University of California