

# Technology Development Group

# Available Technologies

# Contact Our Team

# Permalink

## **Request Information**

# Backfire-to-endfire Leaky-wave Antenna

Tech ID: 20312 / UC Case 2003-251-0

## SUMMARY

UCLA researchers in the Department of Electrical Engineering have developed, reduced to practice and characterized a broadband backfire-toendfire microstrip antenna.

## BACKGROUND

Conventional leaky-wave antennas use higher-order modes to frequency scan and as a consequence are limited to scanning half-space (broadside-to-endfire). In addition, special feeding structures must be added to suppress the dominant frequency mode. These additional elements increase the systems size and cost.

#### **INNOVATION**

There has been an emerging proliferation of interest in new man-made materials with unique properties that cannot be found in nature. These materials are referred to as meta-materials or left-handed media. First proposed by Veselago in the 60s, these materials possess a negative permittivity and permeability resulting in a negative refractive index. The negative refractive index results in electromagnetic radiation being focused by a flat lens versus being dispersed. This and other unique properties could enable unprecedented levels of RF/optical device and antenna miniaturization. A novel circuit design that utilizing the unique properties of left-handed transmission lines (essentially a high-pass filter with phase advance) along with conventional right-handed transmission lines (low-pass filter with phase lag). The resulting design is a new class of antennas that has many interesting applications e.g. antenna arrays. Compared to conventional higher-mode antennas this innovative antenna operates in the dominant mode and does not require any special feeding structure thus reducing size and cost.

#### STATE OF DEVELOPMENT

A novel leaky wave antenna with the capability of scanning from backfire-to-endfire has been demonstrated and characterized. This novel antenna has demonstrated a broad bandwidth of 61% (6 dB gain maintained across the full frequency range) compared to conventional leaky wave antennas.

### ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

- Self-biased Receiver System
- Polarization Standing Wave Cavity Assisted By Anisotropic Structures

# Gateway to Innovation, Research and Entrepreneurship

**UCLA Technology Development Group** 10889 Wilshire Blvd., Suite 920,Los Angeles,CA 90095 https://tdg.ucla.edu Tel: 310.794.0558 | Fax: 310.794.0638 | ncd@tdg.ucla.edu © 2010 - 2016, The Regents of the University of California Terms of use **Privacy Notice** 



### CONTACT UCLA Technology Development Group

ncd@tdg.ucla.edu tel: 310.794.0558.



### **INVENTORS**

Itoh, Tatsuo

#### **OTHER INFORMATION**

**KEYWORDS** communications

**CATEGORIZED AS** Communications Wireless

**RELATED CASES** 2003-251-0