

[Request Information](#)

[Permalink](#)

## Microfluidic Device for Cell Separation Using Dielectrophoresis and/or Magnetohydrodynamics

Tech ID: 21349 / UC Case 2006-426-0

### CONTACT

Alvin Viray  
aviray@uci.edu  
tel: 949-824-3104.



### INVENTORS

- » Flanagan, Lisa A.
- » Lee, Abraham P.
- » Marchenko, Svyatoslav
- » Monuki, Edwin S.
- » Wang, Lisen

### OTHER INFORMATION

#### KEYWORDS

microfluidic, DEP, dielectrophoresis, magnetohydrodynamics, MHD, cell separation

#### CATEGORIZED AS

- » **Biotechnology**
- » Other
- » **Medical**

## BRIEF DESCRIPTION

Researchers at the University of California, Irvine have developed a microfluidic device that has a combination of side wall and planar electrodes designed to generate magnetohydrodynamics (MHD) and dielectrophoresis (DEP) forces on cells in solution. The MHD and DEP forces can separate a heterogeneous population of cells based on their different dielectric properties and sizes.

## FULL DESCRIPTION

The device comprises of a main channel with two side walls and a bottom surface. A plurality of vertically-oriented electrodes is disposed on the first wall and on the second wall opposite to the first wall. As cells flow down the channel containing the two side walls, the electrodes are used to generate DEP and MHD forces vertical to the main stream of the flow. Different cell populations will be subjected to different forces from the opposing electrode arrays affecting the separation of different cell populations and thus resulting in lateral separation of the cells. The cells then can be separated by DEP switching to direct them either into additional channels for further separation or wells for collection.

## SUGGESTED USES

This device may be used to separate heterogeneous cell populations for research, diagnostic, and treatment purposes.

## ADVANTAGES

Cells can be separated laterally along the channel direction and then automatically directed to the downstream channel branches for collection or further separation. Unlike FACS, the cells are not required to be modified for separation.

## STATE OF DEVELOPMENT

Prototypes have been made.

## TESTING

Prototypes have been shown to separate different populations of cells.

## RELATED MATERIALS

» This invention has a patent pending and the pending patent is published as US 2007/0125941

## PATENT STATUS

Country	Type	Number	Dated	Case
United States Of America	Issued Patent	7,964,078	06/21/2011	2006-426

## ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

- ▶ New Microwell Plate Configurations to Increase Microwell Density
- ▶ Multi Layered Microfluidic Devices For In Vitro Large Scale Perfused Capillary Networks
- ▶ Controlled 'One-Cell-One-Bead' Encapsulation in Droplets
- ▶ Microfluidic Flow Transducer Based on the Measurement of Electrical Admittance
- ▶ Microfluidic device for multiplex diagnostics / Microfluidic devices and methods
- ▶ On-Demand Cell Encapsulation Using On-Demand Droplet Generation and Impedance-based Detection
- ▶ High throughput and precision cell sorting
- ▶ High-throughput Microfluidic Research Platform for Performing Versatile Single-Cell Molecular Timed-Release Assays within Droplets
- ▶ Generation Of Choroid Plexus Epithelial Cells From Human Embryonic Stem Cells

- » Devices
- » Diagnostics
- » Research Tools

### » **Research Tools**

- » Other

### » **Sensors & Instrumentation**

- » Scientific/Research

### » **Engineering**

- » Other

## RELATED CASES

2006-426-0

**UCI** Beall  
Applied Innovation

5270 California Avenue / Irvine, CA  
92697-7700 / Tel: 949.824.2683



© 2011, The Regents of the University of  
California  
[Terms of use](#)  
[Privacy Notice](#)