

Technology Development Group

Available Technologies

Contact Our Team

UCLA Technology Development

CONTACT

ncd@tdg.ucla.edu tel: 310.794.0558.

Group

Permalink

Request Information

Charge Storage Device Architecture For Increased Energy And Power Density

Tech ID: 21605 / UC Case 2009-392-0

SUMMARY

Researchers at UCLA have developed an electrochemical capacitor that provides superior energy and power densities through utilizing nanocrystal porous films that provide high surface area and enhanced ionic motion.

BACKGROUND

Electrochemical capacitors are energy storage devices that provide a high-power and lightweight alternative to rechargeable industrial batteries and backup power supplies. Furthermore, the capacitors exhibit high cycling efficiency, fast recharge capability, and reliable cold temperature performance. However, current electrochemical capacitors are limited by their relatively low energy densities.

INNOVATION

Researchers at UCLA have developed a method that significantly increases the energy density of electrochemical capacitors. High surface area and facile ion motion is attained through fabricating nano-crystalline films with three-dimensionally interconnected porosity. As a result, the charge capacity is increased, without compromising the high charging/discharging rates of electrochemical capacitors.

APPLICATIONS

- Uninterrupted power supplies
- Pulse-based communication system, radar, and laser
- Hybrid electric automobiles

ADVANTAGES

- High power density
- High energy density
- Long cycle life
- High charging/discharging rates
- Light weight

STATE OF DEVELOPMENT

Mesoporous nanocrystal-based films have been synthesized and the electrochemical capacitors characterized.

PATENT STATUS

| Country | Туре | Number | Dated | Case |
|--------------------------|---------------|------------|------------|----------|
| United States Of America | Issued Patent | 11,978,591 | 05/07/2024 | 2009-392 |
| United States Of America | Issued Patent | 10,741,337 | 08/11/2020 | 2009-392 |
| United States Of America | Issued Patent | 9,653,219 | 05/16/2017 | 2009-392 |
| United States Of America | Issued Patent | 8,675,346 | 03/18/2014 | 2009-392 |



INVENTORS

Dunn, Bruce S.

OTHER INFORMATION

KEYWORDS chemicals, devices, electrical, nanotechnology, process/procedure, electrical, energy storage, pseudocapacitor, electrochemical capacitor

CATEGORIZED AS

Energy
Storage/Battery

RELATED CASES 2009-392-0

- ▶ "Templated Nanocrystal-Based Porous TiO2 Films for Next-Generation Electrochemical Capacitors," T. Brezesinski, J. Wang, J. Polleux,
- B. Dunn, S. H. Tolbert J. American Chemical Society (2009)

ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

- Cleaning Lithium to Improve Protective Layer
- > Thermally Insulating Transparent Barrier (THINNER) coatings with high transmission, thermal and radiative resistance
- Protective Film for Lithium Electrodes

Gateway to Innovation, Research and Entrepreneurship

UCLA Technology Development Group

10889 Wilshire Blvd., Suite 920,Los Angeles,CA 90095 https://tdg.ucla.edu Tel: 310.794.0558 | Fax: 310.794.0638 | ncd@tdg.ucla.edu © 2011 - 2024, The Regents of the University of California Terms of use Privacy Notice

