# Berkeley PIRA

**Request Information** 

# A NEW CODING TECHNIQUE FOR INTERFERENCE MITIGATION

Tech ID: 24710 / UC Case 2015-078-0

# PATENT STATUS

Country	Туре	Number	Dated	Case
Hong Kong	Issued Patent	HK1242862	07/09/2021	2015-078
United States Of America	Issued Patent	11,018,795	05/25/2021	2015-078
India	Published Application	30/2017	07/28/2017	2015-078

### Additional Patents Pending

# **BRIEF DESCRIPTION**

#### Background

For high data rates and massive connectivity, the next generation cellular networks are expected to deploy many small base stations. While such dense deployment provides the benefit of bringing radio closer to end users, it also increases the amount of interference from neighboring cells. Consequently, smart management of interference is becoming a key enabling technology for high-spectral-efficiency, low-power, broad-coverage wireless communication. Over the past decades, several techniques at different protocol layers have been proposed to mitigate adverse effects of interference in wireless networks. One important conceptual technique at the physical layer is simultaneous decoding whereby each receiver decodes for the desired signal as well as part or whole of interference.

When interference is strong this simultaneous decoding technique achieves the optimal performance for the two user Gaussian interference channel using good point-to-point codes. Moreover, it achieves the optimal maximum likelihood decoding performance in general, when the encoders are restricted to point-to-point random code ensembles. The celebrated Han-Kobayashi coding scheme, which achieves the best known performance for general two-user interference channels, also uses simultaneous decoding as a crucial component. As a main drawback, however, each receiver in simultaneous decoding has to employ some form of multiuser sequence detection, which usually requires high computational complexity to implement.

#### **Technology Description**

Engineers from the University of California have developed a low-complexity coding foundation for communication channels with multiple pairs of senders and receivers, in which the signals from the senders interfere with each other and thus the signal observed at each receiver is a mix of the desired signal as well as one or more interfering signals and some noise. This technology will mitigate the adverse effect of interference caused by other communicating parties.

More specifically, this technology decomposes a data stream into multiple substreams. These substreams are communicated over multiple units ("blocks") of the span of time/frequency/space dimensions. Each sender encodes each of its substreams into a codeword that spans over multiple blocks and transmits multiple codewords simultaneously by superimposing them in a staggering manner. The characteristics of the codewords (coded modulation) and the mechanism of superimposing them (superposition) can be optimized with respect to the communication channel parameters as well as other transmission constraints. Each receiver recovers the codewords from its desired sender as well as some

# Permalink

# CONTACT

Laleh Shayesteh lalehs@berkeley.edu tel: 510-642-4537.



# INVENTORS

» Sasoglu, Eren

# OTHER INFORMATION

### KEYWORDS

cellular, base station, wireless, wireless network, physical layer, receiver, communication, 5G, mobile, telecommunications standard, tactile internet, wi-fi, IEEE, peak bit rate, network

## CATEGORIZED AS

» Communications

» Wireless

**RELATED CASES** 2015-078-0 codewords from interfering senders by decoding its received signal over a sliding window of multiple blocks. For each window, multiple

codewords (both desired and interfering) can be recovered one by one (successive cancellation decoding), which allows for each decoding

step to be low-complexity. The selection of the codewords to be recovered as well as their decoding order can be optimized.

#### SUGGESTED USES

- » 5G cellular systems
- » Wi-fi systems

#### ADVANTAGES

>>> Successfully mitigates adverse effects of interference in wireless networks

» Ability to transmit multiple codewords simultaneously

#### RELATED MATERIALS

» Lele Wang, Eren Sasoglu, Young-Han Kim. Sliding-Window Superposition Coding for Interference Networks. (2014 IEEE International

Symposium on Information Theory) - 01/01/2014

» Hosung Park, Young-Han Kim, Lele Wang. Interference Management via Sliding-Window Superposition Coding. (Globecom 2014) -01/01/2014



University of California, Berkeley Office of Technology Licensing 2150 Shattuck Avenue, Suite 510, Berkeley,CA 94704 Tel: 510.643.7201 | Fax: 510.642.4566 https://ipira.berkeley.edu/ | otl-feedback@lists.berkeley.edu © 2014 - 2021, The Regents of the University of California Terms of use | Privacy Notice