



This technology is currently not available for licensing

Tech ID: 27641

ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

- ▶ Etching Technique for the Fabrication of Thin (Al, In, Ga)N Layers
- ▶ Lateral Growth Method for Defect Reduction of Semipolar Nitride Films
- ▶ Vertical Cavity Surface-Emitting Lasers with Continuous Wave Operation
- ▶ Eliminating Misfit Dislocations with In-Situ Compliant Substrate Formation
- ▶ III-Nitride-Based Vertical Cavity Surface Emitting Laser (VCSEL) with a Dielectric P-Side Lens
- ▶ Aluminum-cladding-free Nonpolar III-Nitride LEDs and LDs
- ▶ Low-Cost Zinc Oxide for High-Power-Output, GaN-Based LEDs (UC Case 2010-183)
- ▶ Defect Reduction in GaN films using in-situ SiNx Nanomask
- ▶ Enhanced Light Extraction LED with a Tunnel Junction Contact Wafer Bonded to a Conductive Oxide
- ▶ Low Temperature Deposition of Magnesium Doped Nitride Films
- ▶ Transparent Mirrorless (TML) LEDs
- ▶ Improved GaN Substrates Prepared with Ammonothermal Growth
- ▶ Optimization of Laser Bar Orientation for Nonpolar Laser Diodes
- ▶ Method for Enhancing Growth of Semipolar Nitride Devices
- ▶ Ultraviolet Laser Diode on Nano-Porous AlGaN template
- ▶ Growth of Polyhedron-Shaped Gallium Nitride Bulk Crystals
- ▶ Nonpolar III-Nitride LEDs With Long Wavelength Emission
- ▶ Improved Fabrication of Nonpolar InGaN Thin Films, Heterostructures, and Devices
- ▶ Growth of High-Quality, Thick, Non-Polar M-Plane GaN Films
- ▶ High-Efficiency, Mirrorless Non-Polar and Semi-Polar Light Emitting Devices
- ▶ Method for Growing High-Quality Group III-Nitride Crystals
- ▶ Controlled Photoelectrochemical (PEC) Etching by Modification of Local Electrochemical Potential of Semiconductor Structure
- ▶ Technique for the Nitride Growth of Semipolar Thin Films, Heterostructures, and Semiconductor Devices
- ▶ MOCVD Growth of Planar Non-Polar M-Plane Gallium Nitride
- ▶ Methods for Fabricating III-Nitride Tunnel Junction Devices
- ▶ Low-Droop LED Structure on GaN Semi-polar Substrates
- ▶ Contact Architectures for Tunnel Junction Devices
- ▶ Semi-polar LED/LD Devices on Relaxed Template with Misfit Dislocation at Hetero-interface
- ▶ Semipolar-Based Yellow, Green, Blue LEDs with Improved Performance
- ▶ III-Nitride-Based Devices Grown On Thin Template On Thermally Decomposed Material

- ▶ Growth of Semipolar III-V Nitride Films with Lower Defect Density
- ▶ III-Nitride Tunnel Junction LED with High Wall Plug Efficiency
- ▶ Tunable White Light Based on Polarization-Sensitive LEDs
- ▶ Cleaved Facet Edge-Emitting Laser Diodes Grown on Semipolar GaN
- ▶ Growth of High-Performance M-plane GaN Optical Devices
- ▶ Packaging Technique for the Fabrication of Polarized Light Emitting Diodes
- ▶ Improved Anisotropic Strain Control in Semipolar Nitride Devices
- ▶ Novel Multilayer Structure for High-Efficiency UV and Far-UV Light-Emitting Devices
- ▶ III-V Nitride Device Structures on Patterned Substrates
- ▶ Method for Increasing GaN Substrate Area in Nitride Devices
- ▶ High-Intensity Solid State White Laser Diode
- ▶ Nitride Based Ultraviolet LED with an Ultraviolet Transparent Contact
- ▶ GaN-Based Thermoelectric Device for Micro-Power Generation
- ▶ Limiting Strain-Relaxation in III-Nitride Heterostructures by Substrate Patterning
- ▶ LED Device Structures with Minimized Light Re-Absorption
- ▶ Growth of Planar Semi-Polar Gallium Nitride
- ▶ High-Efficiency and High-Power III-Nitride Devices Grown on or Above a Strain Relaxed Template
- ▶ UV Optoelectronic Devices Based on Nonpolar and Semi-polar AlInN and AlInGaN Alloys
- ▶ Defect Reduction of Non-Polar and Semi-Polar III-Nitrides
- ▶ III-Nitride Based VCSEL with Curved Mirror on P-Side of the Aperture
- ▶ Enhancing Growth of Semipolar (Al,In,Ga,B)N Films via MOCVD

