

Technology & Industry Alliances Available Technologies Contact Us **Request Information** Permalink **Frequency-Based Filtering of Mechanical Actuation** CONTACT Donna M. Cyr Tech ID: 28675 / UC Case 2012-086-0 cyr@tia.ucsb.edu tel: . **BRIEF DESCRIPTION** Researchers at the University of California, Santa Barbara have created a device that delivers pressure or displacement to specific locations based on the frequency of the actuator used as input. **INVENTORS** Begley, Matthew R. BACKGROUND Collino, Rachel Fluidic devices are used for a variety of applications. However, controlling flow in these devices, such as in ones **OTHER INFORMATION** exclusively using active valve structures such as MEMS structures, can be extremely expensive, decrease reliability, **KEYWORDS** or prevent objectives such as disposability or rapid replacement. indansens, indmicroelec DESCRIPTION **CATEGORIZED AS** Researchers at the University of California, Santa Barbara have created a device that delivers pressure or Engineering displacement to specific locations based on the frequency of the actuator used as input. The device serves as a Engineering mechanical filter where excitation applied at one frequency is delivered to a specific output location with a magnitude Other that depends on the excitation frequency. By modulating the dimensions of the device's fluidic network, and the **RELATED CASES** mechanical response of the deformable features serving as the input and outputs, one can construct different types of 2012-086-0 filters: low-pass, band-pass, or high pass. There are many advantages to using a fluidic network for filtering and actuation. The filtering/actuation system can be re-used with multiple chips and the frequency-specific response of the actuating system can be designed to generate large displacement amplitudes that can be translated onto the chip. **ADVANTAGES** Frequency response can be modulated without altering channels of the microfluidic chip A single input actuator can selectively control flow

Filtering/actuation system can be re-used with multiple chips

APPLICATIONS

Chemical analysis or assay

PATENT STATUS

Country	Туре	Number	Dated	Case
United States Of America	Issued Patent	9,987,576	06/05/2018	2012-086
Patent Cooperation Treaty	Published Application	WO2014/093360	06/19/2014	2012-086

ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

Devices and Methods for 3D Printing of Highly Ordered Composite Materials

University of California, Santa Barbara Office of Technology & Industry Alliances 342 Lagoon Road, ,Santa Barbara,CA 93106-2055 www.tia.ucsb.edu	y	in	© 2017 - 2018, The Regents of the University of California Terms of use Privacy Notice
Tel: 805-893-2073 Fax: 805.893.5236 padilla@tia.ucsb.edu			