Request Information

Process to Synthesize Size Controlled Nanocrystalline Materials for Battery Electrodes

Tech ID: 29138 / UC Case 2012-116-0

BACKGROUND

Lithium Iron Phosphate (LFP) is an excellent cathode for lithium-ion batteries because of its thermal and chemical stability, low cost, good cycle stability and low toxicity. LFP is hindered by lower rate capacity because of its poor electronic conductivity and lithium-ion diffusivity. Typical methods used to produce LFP particles result in heterogeneities that act as stress concentrators resulting in lower battery life.

BRIEF DESCRIPTION

Researchers at UCR have developed a scalable and affordable process for synthesizing nanostructure materials like LiFePO₄ (LFP) at low temperatures (150 to 200 $^{\circ}$ C) with highly reproducible sizes and morphologies. The nanocrystalline structures may be utilized as active elements in battery cathodes or anodes to enhance charging cycle stability or enhance capacitance (including when doped with conductive metals).

The process is performed at relatively low temperatures, and uses environmentally friendly solvents. This results in lower up front and ongoing manufacturing costs in cathode and anode production. The particle size and shape, as well as crystal orientation of the produced structures can be controlled, not only preventing loss of performance and capacity due to increased stresses and charge de-stabilization, but also improving rate capability. The nanostructures created with this method will result in increased battery power and energy density.



Fig. 1: Reproducible nanoprism crystal morphologies produced via the method described here.

Find Technologies



Permalink

CONTACT

Venkata S. Krishnamurty venkata.krishnamurty@ucr.edu tel: .

OTHER INFORMATION

KEYWORDS lithium ion, low temperature, electrode, anode, cathode, precision, energy, storage, LFP, battery, renewable, LiFePO4

CATEGORIZED AS

Energy
Storage/Battery
Nanotechnology
Materials

RELATED CASES 2012-116-0



Fig. 2: Reproducible nanobelt crystal morphologies produced via the method described here.

ADVANTAGES

- ▶ Controlled particle size and shape, as well as crystal orientation of the produced structures.
- > Prevention of loss of performance and capacity due to lower stresses and charge de-stabilization, as well as improved rate capability.
- > The process is performed at relatively low temperatures and uses environmentally friendly solvents.
- ▶ Lower up front and ongoing manufacturing costs in cathode and anode production.
- > The nanostructures created with this method will result in increased battery power and energy density.

SUGGESTED USES

This low cost, low temperature and environmentally-friendly process may be used in the scalable manufacture of active

materials for batteries, including both cathodes and anodes. These nanomaterials have use in batteries for renewable

energy and power grid storage applications.

PATENT STATUS

Country	Туре	Number	Dated	Case
United States Of America	Issued Patent	9,586,822	03/07/2017	2012-116

INVENTIONS BY PROF. DAVID KISAILUS

Please see all inventions by Prof. David Kisailus and his team at UCR

RELATED MATERIALS

Solvothermal Synthesis, Development, and Performance of LiFePO4 Nanostructures

University of California, Riverside Office of Technology Commercialization 200 University Office Building, Riverside,CA 92521 otc@ucr.edu https://research.ucr.edu/

Terms of use | Privacy Notice | © 2018 - 2022, The Regents of the University of California