

# High-Frequency Imaging and Data Transmission Using a Re-configurable Array Source with Directive Beam Steering

Tech ID: 32523 / UC Case 2021-652-0

# ABSTRACT

Researchers at the University of California, Davis have developed a reconfigurable radiator array that produces a high frequency directed beam via uninterrupted, scalable, electronic beam steering.

## **FULL DESCRIPTION**

Data transmission and scanning applications would both benefit from the potential opportunities inherent in the use of very high frequency electromagnetic wavelengths. Faster and larger data transfers and higher-resolution imaging could provide advantages ranging from improved mobile phone reception to the more rigorous screening of humans and objects for national security purposes. However, capturing the advantages of terahertz frequency electromagnetic waves has proven problematic historically. Concerns range from high power consumption requirements to the loss of resolution and "blind spots" that can occur during transmission. Options developed to address these concerns – including the use of directed beams or larger lenses – all have their own limitations.

Researchers at the University of California, Davis have overcome many historical concerns by coupling lens-integrated, reconfigurable, radiating, individual light beams into a reconfigurable array structure. This array structure can perform continuous, uninterrupted and scalable electronic beam steering with high directivity in a lens-coupled source array. The technology combines two, different, methods of beam steering: antenna displacement and phase shifting. The result is lower power functionality with both high directivity and fine scanning resolution.

The technology includes a silicon wafer with an integrated array of pixel sources comprising unit cells. Each unit cell in the integrated array comprises a standing wave oscillator (SWO), but is coupled to neighboring unit cells in both horizontal and vertical directions. This configuration makes it possible to turn individual unit cells on and off, thus creating phase shifts between the adjacent unit cells. As a result, a directed beam can be steered to cover a blind spot between adjacent beams produced by the unit cells. Furthermore, the technology is capable of multibeam/frequency radiation by simultaneous activation of subarrays without intersecting corners. This method of beam steering using a reconfigurable array in a lens-coupled source can also be generalized and employed in other settings. Thus, this technology is applicable at both different frequencies and with other types of unit cell sources. This method of beam steering can also be used in different types of wireless systems, but is particularly well suited for applications such as high-resolution imaging.

#### **APPLICATIONS**

- Imaging systems
- Next-generation voice and data transmission

# **FEATURES/BENEFITS**

# CONTACT

Andrew M. Van Court amvancourt@ucdavis.edu tel: .



## INVENTORS

- Jalili, Hossein
- Momeni, Omeed

# OTHER INFORMATION

KEYWORDS electronic beam-steering, high-resolution imaging, integrated radiator and phased array circuits, reconfigurable array, silicon lens, coupled voltage-controlled (VCO) and standing wave (SWO) oscillators

#### CATEGORIZED AS

Optics and
Photonics
All Optics and

- Photonics
- Communications
  - Optical
  - Wireless

- Achieves narrow beams, resulting in high resolution
- Minimizes interference and signal loss
- ▶ Uses significantly less power compared to alternate approaches for terahertz applications

#### **PATENT STATUS**

Country	Туре	Number	Dated	Case
United States Of America	Published Application	20220247075	08/04/2022	2021-652

Additional Patent Pending

#### Imaging

- ▶ Other
- Security
- Medical
  - Imaging
- Security and

# Defense

## 

Screening/Imaging

Engineering

Other

# **RELATED CASES**

2021-652-0

# ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

- Reversed Feedback Amplifier Architecture
- ▶ Ultra-High Range Resolution Doppler Radar Front End With Quadrature-Less Coherent Demodulation
- Field Effect Bipolar Transistor
- Low Energy and Noise Sub-Sampling Phase-Locked Loop
- ▶ Hybrid Electromechanical Metamaterials for Optical and Electrical Devices
- Phased-Locked Loop Coupled Array for Phased Array Applications
- Scalable Phased Array Standing Wave Architecture
- Embedded Power Amplifier
- Reducing Electrical Current Variations in Phase-Locked Loop Systems

University of California, Davis	Tel:	© 2021 - 2022, The Regents of th	ne University of
Technology Transfer Office	530.754.8649		California
1 Shields Avenue, Mrak Hall 4th Floor,	techtransfer@ucdavis.	<u>edu</u>	Terms of use
Davis,CA 95616	https://research.ucdavis.edu/technology-		Privacy Notice
	transfer/		
	Fax:		
	530.754.7620		