**Find Technologies** 

Contact Us

Permalink

**Request Information** 

# Porobello Mushroom Based Hierarchically Porous Carbon Nanoribbons And Architectures

Tech ID: 32654 / UC Case 2015-444-0

# PATENT STATUS

Country	Туре	Number	Dated	Case
United States Of America	Issued Patent	10,818,914	10/27/2020	2015-444
FULL DESCRIPTION				

### Background

The industry standard for rechargeable lithium-ion battery anode is synthetic graphite due in part to its high cycling ability and low hysteresis. The disadvantages of graphite are it is relatively expensive and has relatively lower lithium storage capacity per carbon weight. Hard carbon anodes offer a good alternative in comparison with graphite due to its higher specific capacity (~ 500 mAh/gram) though they have significant irreversible capacity. Carbon anodes derived from biomass are of interest because of their low cost and environmental benignity.

#### **Current Invention**

Biologically inspired, the research team led by Prof(s). Cengiz Ozkan and Mihrimah Ozkan studied the tissues of Portobello Mushroom and the electrochemical performance of the pyrolytic carbons derived from these tissues. Their research led to the discovery and synthesis of a patented, novel, free-standing, carbon anodes derived from the cap skin tissue (CST) of the mushroom. Pyrolysis of the CST, at temperatures of 900 – 1100 deg. C resulted in a morphology of interconnected network of hierarchically porous carbon nanoribbons.



Transmission Electron Microscopy image of CST processed at 1100 deg. C showing hierarchically porous nanoribbons



CONTACT

Venkata S. Krishnamurty venkata.krishnamurty@ucr.edu tel: .

#### **OTHER INFORMATION**

**KEYWORDS** 

Hard carbon, Carbon anode, Lithium-

ion battery, Energy storage, Portobello

Mushroom, Nanoribbon,

Nanostructures

QUICKSTART LICENSING



This technology is available through the UC QuickStart program for startups.

**CATEGORIZED AS** 

Energy

Storage/Battery

Materials & Chemicals

Biological

Nanomaterials

**RELATED CASES** 

2015-444-0

Charge-discharge plot and coulombic efficiency of carbon anode derived from CST processed at 1100 deg. C.

# **ADVANTAGES**

The novelty and significance of their discovery are:

- > A binder free, additive free, and current collector free, carbon anode.
- ▶ Minimal processing and naturally self-activating.
- ► Higher energy density.
- Lower cost and lower environmental impact.

## SUGGESTED USES

- Lithium-ion battery anode
- Rechargeable energy storage

## TESTING

The team fabricated 2032 type coin cells to test the performance of the carbon anodes. The CSTs processed at temperature of 1100 deg. C

displayed the optimum performance with initial discharge capacity of 771.3 mAh/gram, 99.75% coulombic efficiency after 700 cycles.

# **RELATED MATERIALS**

▶ Bio-Derived, Binderless, Hierarchically Porous Carbon Anodes for Li-ion Batteries

University of California, Riverside Office of Technology Commercialization 200 University Office Building, Riverside,CA 92521 otc@ucr.edu https://research.ucr.edu/

Terms of use | Privacy Notice | © 2021 - 2022, The Regents of the University of California