

Request Information

Permalink

## Method to Improve the Accuracy of an Independently Acquired Flow Velocity Field Within a Chamber, Such as a Heart Chamber

Tech ID: 32959 / UC Case 2022-994-0

### BRIEF DESCRIPTION

Currently available techniques used to measure velocimetry within chambers, such as heart chambers, are prone to error due to the inherent limitations of imaging and computational modalities. UC Irvine researchers have developed a novel method that significantly improves the accuracy of velocimetry techniques inside a chamber regardless of the modality.

### SUGGESTED USES

·Measuring blood flow pattern in heart chambers via echocardiography

### FEATURES/BENEFITS

·Improves accuracy of 3D velocity flow field

### FULL DESCRIPTION

Heart diseases have unique blood flow characteristics, and any variation in the blood flow pattern may indicate a change in the overall cardiac performance. Existing echocardiography methods used to quantify blood flow often use two-dimensional (2D) blood flow information to assess cardiac dysfunction. While useful, this information does not provide sufficient accuracy for characterizing complex three-dimensional (3D) flows, such as the flows in hearts with congenital defects or in pulmonary hypertension. However, the quantification of 3D cardiac flow patterns has remained a challenging fluid dynamics problem and modern echocardiography-based velocimetry techniques cannot yet acquire data with sufficient spatial and temporal resolutions to improve clinical diagnosis.

Researchers at University of California, Irvine have invented a novel method that significantly improves the accuracy of velocimetry techniques in measuring 3D flow velocity in chambers, such as heart chambers.

### STATE OF DEVELOPMENT

The computer code has been developed and validated.

### PATENT STATUS

Country	Type	Number	Dated	Case
United States Of America	Published Application	20240020841	01/18/2024	2022-994

### CONTACT

Alvin Viray  
aviray@uci.edu  
tel: 949-824-3104.



### INVENTORS

» Kheradvar, Arash

### OTHER INFORMATION

### KEYWORDS

Particle image velocimetry, Particle tracking methods, Vector flow mapping, 4D flow MRI, Conservation of mass, Incompressibility, Blood flow, Cardiac flow, Cardiac fluid mechanics, Biofluid mechanics

### CATEGORIZED AS

» **Medical**

» Devices

» Disease:

Cardiovascular and Circulatory System

**ADDITIONAL TECHNOLOGIES BY THESE INVENTORS**

- ▶ Percutaneous Heart Valve Delivery System Enabling Implanted Prosthetic Valve Fracture
- ▶ A distensible wire mesh for a cardiac sleeve
- ▶ Percutaneous Heart Valve Delivery System
- ▶ Growth-Accommodating Transcatheter Pulmonary Valve System
- ▶ System for Transcatheter Grabbing and Securing the Native Mitral Valve's Leaflet to a Prosthesis
- ▶ Real-time 3D Image Processing Platform for Visualizing Blood Flow Dynamics
- ▶ Method for Synchronizing a Pulsatile Cardiac Assist Device with the Heart
- ▶ Automated Histological Image Processing tool for Identifying and Quantifying Tissue Calcification
- ▶ Fully Automated Multi-Organ Segmentation From Medical Imaging
- ▶ Simple, User-friendly Irrigator Device for Cleaning the Upper Aerodigestive Tract and Neighboring Areas
- ▶ Automated 3D Reconstruction of the Cardiac Chambers From MRI or Ultrasound
- ▶ Minimally Invasive Percutaneous Delivery System for a Whole-Heart Assist Device

**UCI Beall**  
Applied Innovation

5270 California Avenue / Irvine, CA  
92697-7700 / Tel: 949.824.2683



© 2022 - 2024, The Regents of the University of  
California  
[Terms of use](#)  
[Privacy Notice](#)