



III-Nitride-Based Vertical Cavity Surface Emitting Laser (VCSEL) with a Dielectric P-Side Lens

Tech ID: 33105 / UC Case 2023-847-0

BACKGROUND

Gallium nitride (GaN) vertical cavity surface emitting lasers (VCSELs) have attracted attention with their ability to emit in visible and ultraviolet (UV) wavelengths, affording a wide swath of exciting new applications in displays, solid-state lighting, sensing, and communications. Visible light communications (VLC) is a particularly attractive application for GaN VCSELs where they can be coupled with a phosphor to act as both a light source and data transmission device simultaneously. With the extensive proliferation of devices that can access networks, efficient data transmission has become a high priority, especially as bandwidths are becoming overcrowded. Realizing data transmission at visible wavelengths would greatly expand current bandwidth capabilities, but achieving this task will require solutions to the device degradation caused during lens growth and absorption loss within the long cavities of GaN VCSELs.

DESCRIPTION

Researchers at the University of California, Santa Barbara have produced a GaN VCSEL that achieves high efficiency, high peak power, and long device lifetimes by eliminating degradation to the active region, improving emission intensity, and significantly reducing absorption loss within the cavity. Key to the invention is the topside dielectric p-side lens which provides the mode control characteristics. Topside fabrication eases pain points with processing and alignment in addition to putting more distance between the active region and the planar DBR. The topside lens allows for the active region to be farther up in the cavity, increasing the maximum width of the beam and current aperture. The use of wider apertures enables higher packing densities, positioning this VCSEL design especially well for high-power directional lighting applications or other applications where an array of VCSELs with a wide divergence angle is of interest.

ADVANTAGES

- ▶ Improved VCSEL performance
- ▶ Dramatically increased output power
- ▶ Reduced threshold current density
- ▶ Increased device lifetimes

APPLICATIONS

- ▶ VCSELs

CONTACT

Pasquale S. Ferrari
ferrari@tia.ucsb.edu
tel: .

INVENTORS

- ▶ Cohen, Daniel A.
- ▶ Gee, Stephen
- ▶ Kearns, Jared A.
- ▶ [Nakamura, Shuji](#)
- ▶ Palmquist, Nathan

OTHER INFORMATION

KEYWORDS

III-nitride-based VCSEL,
Vertical cavity surface emitting
laser, GaN VCSEL, Dielectric
p-side lens, Efficiency
improvement, High peak
power, Long device lifetimes,
Active region degradation,
Emission intensity
improvement, Absorption loss
reduction, Topside fabrication

CATEGORIZED AS

- ▶ **Semiconductors**
 - ▶ [Assembly and Packaging](#)
 - ▶ [Design and Fabrication](#)
 - ▶ [Materials](#)
 - ▶ [Processing and Production](#)

PATENT STATUS

RELATED CASES

2023-847-0

Country	Type	Number	Dated	Case
Patent Cooperation Treaty	Reference for National Filings	WO 2024/044567	02/29/2024	2023-847

Patent Pending

ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

- ▶ Vertical Cavity Surface-Emitting Lasers with Continuous Wave Operation
- ▶ Eliminating Misfit Dislocations with In-Situ Compliant Substrate Formation
- ▶ Methods to Produce and Recycle Substates for III-Nitride Materials with Electrochemical Etching
- ▶ III-Nitride Tunnel Junction with Modified Interface
- ▶ III-Nitride Tunnel Junction LED with High Wall Plug Efficiency
- ▶ Novel Multilayer Structure for High-Efficiency UV and Far-UV Light-Emitting Devices
- ▶ A Method To Lift-Off Nitride Materials With Electrochemical Etch
- ▶ Activation of P-Type Layers of Tunnel Junctions in Micro-LEDs
- ▶ High-Intensity Solid State White Laser Diode
- ▶ Nitride Based Ultraviolet LED with an Ultraviolet Transparent Contact
- ▶ Epitaxial Light Control Features in Light Emitting Diodes
- ▶ High-Efficiency Vertical Cavity Surface Emitting Laser Fabrication
- ▶ A Wafer-Scale, Low Defect Density Strain Relaxed Template for III-Nitride-Based High Efficiency and High-Power Devices
- ▶ High-Efficiency and High-Power III-Nitride Devices Grown on or Above a Strain Relaxed Template
- ▶ III-Nitride Based VCSEL with Curved Mirror on P-Side of the Aperture

