ONE-STEP PACKAGED MULTI-MODE CMOS BIO-ANALYZER FOR POINT-OF-CARE

Tech ID: 33776 / UC Case 2025-042-0

CONTACT

Sabrina N. David
sabrina.david@berkeley.edu
tel: .



INVENTORS

» Chien, Jun-Chau

OTHER INFORMATION

CATEGORIZED AS

» **Optics and Photonics**

» All Optics and Photonics

» **Agriculture & Animal Science**

» Animal Science

» Devices

» Other

» **Biotechnology**

» Health

» Other

» **Engineering**

» Engineering

» Other

» **Materials & Chemicals**

» Biological

» **Medical**

» Diagnostics

» Disease: Autoimmune and Inflammation

» Disease: Blood and Lymphatic System

PATENT STATUS

Country	Type	Number	Dated	Case
Patent Cooperation Treaty	Published Application	WO 2026/107376	05/21/2026	2025-042

BRIEF DESCRIPTION

Current clinical practice for detecting low-concentration molecular biomarkers requires sending samples to centralized labs, leading to high costs and delays. Successful point-of-care (POC) diagnostic technology exist, such as the paper-based lateral-flow assay (LFA) used for pregnancy tests and SARS-CoV-2 rapid antigen tests, or miniaturized instruments such as the Abbot i-Stat Alinity. However, the former provides binary results or limited quantitative accuracy, and the latter is too expensive for in-home deployment. A promising approach for POC diagnostics, offering tailored circuit optimization, multiplexed detection, and significant cost and size reductions, is millimeter-sized CMOS integrated circuits coupled with microfluidics. Recent demonstrations include protein, DNA/RNA, and cell detection. The current complexity of system packaging (e.g., wire/flip-chip bonding) makes integrating microfluidics with more sophisticated functions challenging, and often-required syringe pumps and tubing are operationally unfriendly, limiting current approaches.

UC Berkeley researchers have developed a fully integrated, multi-mode POC device that requires single-step assembly and operates autonomously. Drawing inspiration from RFID technology and implantables, they have introduced inductively-coupled wireless powering and communication functionality into a CMOS bio-analyzer. With the chip being fully wireless, the die can be easily integrated into a substrate carrier, achieving a completely flat surface that allows for seamless bonding with the microfluidic module. In the final product, the device will be sealed in a pouch inside a vacuum desiccator. The user tears the pouch, adds a drop of sample, and the system automatically begins operation. The operation window can last up to 40 minutes, making the process insensitive to time delays. The present CMOS bio-analyzer integrates pH-sensing and amperometric readout circuits for both proton-based and redox-based immunoassays.

SUGGESTED USES

» Point-of-care (POC) diagnostics; detection of low-concentration molecular biomarkers at or near a patient's location

ADVANTAGES

» Seamless integration of CMOS IC and microfluidic components for high-performance, multi-functional point-of-care (POC) diagnostic device

» Single-step assembly, without wire/flip-chip bonding

» Autonomous operation

RELATED MATERIALS

ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

▶ Subtractive Microfluidics in CMOS

» Disease: Digestive System

» Disease: Infectious Diseases

» Other

» Research Tools

» Screening

» **Research Tools**

» Other

» **Semiconductors**

» Assembly and Packaging

» Other

» **Sensors & Instrumentation**

» Biosensors

» Medical

» Other

» Scientific/Research

» **Veterinary**

» Diagnostics

RELATED CASES

2025-042-0

University of California, Berkeley Office of Technology Licensing
2150 Shattuck Avenue, Suite 510, Berkeley,CA 94704
Tel: 510.643.7201 | Fax: 510.642.4566
https://ipira.berkeley.edu/ | otl-feedback@lists.berkeley.edu
© 2025, The Regents of the University of California
Terms of use | Privacy Notice