

Electrolyte Formulations for Non-Aqueous Flow Batteries

Tech ID: 33971 / UC Case 2024-9B8-0

ABSTRACT

Researchers at the University of California, Davis have developed a technology that introduces new electrolyte compositions that significantly enhance the stability and efficiency of nonaqueous flow batteries.

FULL DESCRIPTION

The technology comprises innovative liquid electrolyte solutions for redox flow batteries (RFBs), featuring a mix of specifically chosen cations and anions that improve conductivity, reduce overpotential, and enhance the overall energy efficiency and cycling stability of RFBs. This breakthrough addresses the critical challenges of low energy efficiency and cycling stability in non-aqueous redox flow batteries.

APPLICATIONS

- ▶ Energy storage systems for intermittent renewable energy sources.
- ▶ High-performance batteries for industrial and commercial applications.
- Advanced energy solutions for grid stabilization and peak shaving.

FEATURES/BENEFITS

- ▶ Increases energy density and efficiency of RFBs.
- Improves cycling stability.
- ▶ Reduces ohmic drop and excess energy requirements.
- ▶ Enhances conductivity and lower overpotential.
- Compatibility with a wide range of redox active materials.
- Improves energy efficiency in non-aqueous redox flow batteries.
- Enhances chemical stability and solubility of redox active organic molecules.
- Reduces operational and maintenance costs by increasing cycling stability.

PATENT STATUS

Patent Pending

CONTACT

Victor Haroldsen haroldsen@ucdavis.edu tel: 530-752-7717.



INVENTORS

- Berben, Louise A.
- McIntosh, Jory S.

OTHER INFORMATION

KEYWORDS electrolyte solutions, energy efficiency, cycling stability, redox flow batteries, electrochemical stability, renewable energy storage, highperformance batteries, conductivity improvement, overpotential reduction, non-aqueous flow batteries

CATEGORIZED AS

Energy

Storage/Battery

Engineering

► Engineering

Materials &

Chemicals

- Chemicals
- Composites

RELATED CASES

2024-9B8-0

ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

- ▶ Group 13 Metals as Anolytes in Non-Aqueous, Redox Flow Batteries
- Organoaluminum Flow Battery Analytes

University of California, Davis	Tel:	\odot 2025, The Regents of the University of California	
Technology Transfer Office	530.754.8649		Terms of use
1 Shields Avenue, Mrak Hall 4th Floor,	techtransfer@ucda	vis.edu	Privacy Notice
Davis,CA 95616	https://research.ucdavis.edu/technology-		
	<u>transfer/</u>		
	Fax:		
	530.754.7620		