

Signal Space Based Navigation

Tech ID: 34561 / UC Case 2014-329-0

ABSTRACT

Researchers at the University of California, Davis have developed a navigation system that constructs a sensing map from wireless signal observations and pedestrian deadreckoning (PDR) data to enable accurate indoor navigation without relying on traditional geographic localization maps.

FULL DESCRIPTION

This technology introduces a signal space based navigation apparatus and method that leverages wireless signal clusters, such as WiFi signals, and PDR displacement vectors obtained via crowd-sourced data from mobile user devices. Unlike conventional systems that depend on pre-existing localization maps linking geographic locations, this navigation system builds a topological sensing map that represents locations as clusters of wireless signals connected by mobility information. It detects turns using low-power accelerometers to collect more frequent wireless observations at these locations, improving both accuracy and energy efficiency. The system further uses density-based clustering (e.g., DBSCAN) and fuses PDR traces to establish relative positions between clusters, facilitating route planning and navigation guidance through a user interface.

APPLICATIONS

- ▶ Indoor navigation solutions for shopping malls, airports, hospitals, and large public venues.
- ▶ Enhanced location-aware services in environments with limited GPS accessibility.
- ▶ Mobile applications providing crowd-sourced navigation data for retail and facility management.
- ▶ Assistive technologies for visually impaired users in indoor public spaces.
- ▶ Enterprise asset tracking and workforce navigation in industrial and commercial buildings.

FEATURES/BENEFITS

- ▶ Removes the need for prior geographic knowledge or localization maps.
- ▶ Compatible with existing mobile devices.
- ▶ Constructs autonomous, non-intrusive maps using crowd-sourced wireless and PDR data.
- ▶ Increases energy efficiency by activating higher sensor sampling rates only during detected turns with always-on accelerometers.
- ▶ Mitigates PDR drift and signal fluctuation errors through clustering and trace fusion.
- ▶ Refines wireless clusters adaptively over time to enhance sensing map accuracy.
- ▶ Enables indoor navigation with segmented path instructions generated at turns.
- ▶ Resolves signal fluctuation and PDR drift challenges in mobile device navigation.
- ▶ Reduces energy consumption via adaptive, turn-based sensor sampling.

CONTACT

Michael M. Mueller
mmmueller@ucdavis.edu
 tel: .



INVENTORS

- ▶ Mohapatra, Prasant
- ▶ Zhu, Jindan

OTHER INFORMATION

KEYWORDS

accelerometer, clustering, crowd-sourcing, deadreckoning, indoor navigation, pedestrian navigation, sensing map, turn detection, WiFi clusters, wireless signal

CATEGORIZED AS

- ▶ **Communications**
 - ▶ Wireless
- ▶ **Computer**
 - ▶ Software
- ▶ **Sensors & Instrumentation**
 - ▶ Position sensors

RELATED CASES

2014-329-0

- ▶ Overcomes complexity in mapping sensor data to physical layouts.
- ▶ Simplifies indoor map building by removing the need for manual annotation or user intervention.

PATENT STATUS

Country	Type	Number	Dated	Case
United States Of America	Issued Patent	9,733,088	08/15/2017	2014-329
Patent Cooperation Treaty	Published Application	WO 2015/065375	05/07/2015	2014-329

ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

- ▶ [Individual Identity Verified Through Device-Free, WiFi Based Framework](#)
- ▶ [Sensor-Assisted Facial Authentication System For Smartphones](#)
- ▶ [Energy Efficient Trigger Word Detection via Accelerometer Data](#)
- ▶ [Adversarial Resilient Malware Detector Based on Randomization](#)

University of California, Davis

Technology Transfer Office

1 Shields Avenue, Mrak Hall 4th Floor,
Davis, CA 95616

Tel:

530.754.8649

techtransfer@ucdavis.edu

<https://research.ucdavis.edu/technology-transfer/>

Fax:

530.754.7620

© 2026, The Regents of the University of California

[Terms of use](#)

[Privacy Notice](#)