

Request Information

Permalink

Scalable, Multi-Energy Detection and Imaging

Tech ID: 34721 / UC Case 2025-943-0

BACKGROUND

Comprehensive radiation detection across the spectral range requires distinct systems for ionizing and non-ionizing imaging because each technology faces unique architectural hurdles. Modern visible light detection has successfully transitioned from passive plates to digital Active Pixel Sensors (APS) by leveraging Complementary Metal-Oxide-Semiconductor (CMOS) technology to provide every pixel with its own dedicated amplifier and active circuitry. Ionizing radiation detection like X-ray and gamma-ray has relied on exotic scintillators to convert radiation into light, a process prone to lateral light scattering and degraded spatial resolution. Recent advancements in ionizing radiation have shifted toward direct conversion materials like amorphous selenium (a-Se), which transform X-rays directly into electrical charges. However, these direct-conversion devices do not scale to larger areas without significant noise being a factor. This is primarily due to thin-film transistor (TFT) backplanes which, unlike their CMOS counterparts, lack the local amplification necessary to maintain a high signal-to-noise ratio.

TECHNOLOGY DESCRIPTION

To help address these challenges in comprehensive radiation detection, researchers at UC Santa Cruz (UCSC) have developed a scalable imaging sensor platform. Unlike traditional detectors that require separate systems for different spectral ranges, the UCSC research results feature a modular array of active pixels engineered for concurrent [switchable] detection of ionizing and non-ionizing radiation. This design integrates a local integrated readout circuit monolithically on a substrate, housing an internal photodetector within every pixel. A sensing layer made of chalcogenide or semiconductor crystal material is deposited in a vertical stack directly over the readout circuit and electrically coupled through a conductive contact. This dual-mode and vertical integration enables high-resolution, low-noise imaging across a modular surface area, with each detector tile designed to be closely aligned to adjacent tiles to form larger panel sizes.

APPLICATIONS

- ▶ medical imaging
- ▶ non-destructive testing
- ▶ security screening
- ▶ research tooling

FEATURES/BENEFITS

- ▶ Features modular sensor tiles designed to be closely aligned to adjacent tiles, scalable to larger panel sizes.
- ▶ Integrates micron-scale active pixels directly with a-Se sensing layers eliminates blurring common to scintillator-based devices.
- ▶ Dual-mode integrated circuit readout enables single hardware to perform both X-ray and VisNIR imaging.
- ▶ Monolithic CMOS architecture supports video frame rates and real-time reconstruction.

INTELLECTUAL PROPERTY INFORMATION

Patent Pending

RELATED MATERIALS

CONTACT

Marc Oettinger
marc.oettinger@ucsc.edu
tel: 831-502-0253.



INVENTORS

- ▶ Abbaszadeh, Shiva
- ▶ Farrier, Michael

OTHER INFORMATION

KEYWORDS

amorphous selenium, a-Se, aSe, ionizing radiation, direct conversion, scintillator, active pixel sensor, APS, photodiode, stitching, CMOS, non-ionizing radiation, halide perovskite, radiation detection, radiation, Complementary Metal-Oxide-Semiconductor, medical imaging, non-destructive testing, security screening, thin-film transistor, TFT, spectral range, spectral

CATEGORIZED AS

- ▶ **Imaging**
 - ▶ Medical
- ▶ **Medical**
 - ▶ Imaging
 - ▶ Research Tools
 - ▶ Software
- ▶ **Security and Defense**
 - ▶ Screening/Imaging
- ▶ **Sensors & Instrumentation**
 - ▶ Medical
 - ▶ Scientific/Research

RELATED CASES

2025-943-0

ADDITIONAL TECHNOLOGIES BY THESE INVENTORS

► [Systems and Methods for Identifying Anomalous Nuclear Radioactive Sources](#)

University of California, Santa Cruz

Industry Alliances & Technology Commercialization

Kerr 413 / IATC,

Santa Cruz, CA 95064

Tel: 831.459.5415

innovation@ucsc.edu

<https://officeofresearch.ucsc.edu/>

Fax: 831.459.1658

© 2026, The Regents of the University of California

[Terms of use](#)

[Privacy Notice](#)